

10/632,030

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) ~~A production process for a catalyst~~ A process of producing a catalyst, wherein the catalyst includes including a particulate lump carrier and a catalytic component supported thereon, with, the production process comprising the step of:

carrying out simultaneous ~~revolution~~ revolving and rocking of a treatment container as charged with the a particulate lump carrier and a catalyst precursor including the a catalytic component, thereby supporting such that the said catalytic component ~~into~~ becomes to be supported on the said particulate lump carrier.

2. (currently amended) ~~A production~~ The process according to claim 1, wherein the catalyst precursor is in the form of any one a member selected from the group consisting of a powder including the catalytic component, a solution including the catalytic component, and a suspension including the catalytic component.

3. (currently amended) ~~A production process according to claim 1, wherein:~~

A process of producing a catalyst, the catalyst including a particulate lump carrier and a catalytic component supported thereon, the process comprising the step of:

carrying out simultaneous revolving and rocking of a treatment container charged with a particulate lump carrier and a catalyst precursor including a catalytic component,

{18450.DOC} (Amendment and Remarks--page 3 of 13)

10/632,030

such that said catalytic component becomes to be supported on said particulate lump carrier, wherein:

- a) the treatment container is the shape of a cylinder having a length of 1 to 3 times of its diameter and has a horizontally oriented central axis;
- b) the carrier is charged in an amount of 10 to 60 % of the a capacity of the treatment container;
- c) ~~the revolution is to revolve~~ the step of carrying out simultaneous revolving and rocking revolves the treatment container at 5 to 60 rpm around the central axis; and
- d) ~~the rocking is to rock~~ the step of carrying out simultaneous revolving and rocking rocks the central axis at 1 to 12 spm in an upward and downward rocking angle of 5 to 90°.

4. (new) The process according to claim 3, wherein the catalyst precursor is in the form of a member selected from the group consisting of a powder including the catalytic component, a solution including the catalytic component, and a suspension including the catalytic component.

5. (new) A process of producing a catalyst, the catalyst including a particulate lump carrier and a catalytic component supported thereon, the process comprising the step of:

carrying out simultaneous revolving and rocking of a treatment container charged with a particulate lump carrier and a catalyst precursor including a catalytic component, such that said catalytic component becomes to be supported on said particulate lump carrier, wherein:

- a) the treatment container is the shape of a cylinder having a length of 1 to 3 times of its diameter and has

(18450.DOC) (Amendment and Remarks--page 4 of 13)

10/632,030

- a horizontally oriented central axis;
- b) the carrier is charged in an amount of 10 to 60 % of a capacity of the treatment container;
- c) the step of carrying out simultaneous revolving and rocking revolves the treatment container at 5 to 60 rpm around the central axis; and
- d) the step of carrying out simultaneous revolving and rocking rocks the central axis at 1 to 12 spm in a diametrically opposite rocking angle of 5 to 90°.

6. (new) The process according to claim 5, wherein the catalyst precursor is in the form of a member selected from the group consisting of a powder including the catalytic component, a solution including the catalytic component, and a suspension including the catalytic component.